



SALES FACT SHEET



CLASSIC® 95% A.F.U.E. HIGH EFFICIENCY UPFLOW GAS FURNACES

Features

- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Left or right side gas, electric, and condensate drainage connections on upflow models.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Pre-paint galvanized steel cabinet.
- Molded permanent filters.
- Optional indoor or outdoor combustion air. In addition, combustion air may be piped to either the top or side of the cabinet on all upflow models. A special molded fitting is provided to ease installation.
- Control fuse protection.
- Solid bottom is standard.
- Control board diagnostics.

A variety of cooling coils and plenums designed to use with the Classic® 95% A.F.U.E. gas furnaces are available as optional accessories for air conditioning models.

RGRC- SERIES

Models with Input Rates
from 45,000 to 105,000 BTU/HR
[13.19 to 30.77 kW]

(All Models 95% A.F.U.E.)

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger Limited Lifetime
Conditional Parts (registration required) Ten (10) Years

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGRC-04*MAES	45,000 [13.19]	42,000 [12.31]	885 [417]	1195 [564]	111 [50.3]	
RGRC-06*MAES	60,000 [17.58]	56,000 [16.41]	845 [398]	1100 [519]	117 [53.1]	
RGRC-07*MAES	75,000 [21.98]	70,000 [20.51]	1050 [495]	1100 [519]	124 [56.2]	
RGRC-07*RBGS	75,000 [21.98]	70,000 [20.51]	1500 [708]	1600 [755]	137 [62.1]	
RGRC-09*ZAJ5	90,000 [26.38]	84,000 [24.62]	1640 [774]	1820 [859]	148 [67.1]	
RGRC-10*ZAJ5	105,000 [30.77]	100,000 [30.77]	1445 [682]	1810 [854]	152 [68.9]	

① See Conversion Kit Index Form for high altitude derate.

[] Designates Metric Conversions

